





Building Zone Facilities Management Cable

Applications: Security and Alarm Systems, Intercom/Public Address Systems, Sound & Audio, Simple, Low Voltage Controls, High EMI/RFI Interference Areas (shielded cable only)



8701-8717



8718-8735

Building Zone, Multiconductor Riser-Rated PVC

Multiconductor, Unshielded Riser

Operating Temperature: -20°C to 60°C; 300 Volt; Conductor: Stranded Bare Copper. Insulation: Color-Coded PVC, Shield: Aluminum/Polyester Foil with a tinned copper drain wire, PVC jacket UL Types: CMR, MPR, CL2R, FPLR (22 AWG thru 16 AWG) UL Types: CL2R, FPLR (14 AWG and 12 AWG)

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8701R	2	22	7/30	0.018	0,46	0.13	3,30
8702R	3	22	7/30	0.018	0,46	0.14	3,56
8703R	4	22	7/30	0.018	0,46	0.15	3,81
8704RA	2	20	7/28	0.018	0,46	0.14	3,56
8705R	3	20	7/28	0.018	0,46	0.15	3,81
8706R	4	20	7/28	0.018	0,46	0.17	4,32
8707R	2	18	7/26	0.018	0,46	0.16	4,06
8708R	3	18	7/26	0.018	0,46	0.17	4,32
8709R	4	18	7/26	0.018	0,46	0.19	4,83
8710R	2	16	19/29	0.018	0,46	0.19	4,83
8711R	3	16	19/29	0.018	0,46	0.2	5,08
8712R	4	16	19/29	0.018	0,46	0.22	5,59
8713R	2	14	19/26	0.018	0,46	0.23	5,84
8714R	3	14	19/26	0.018	0,46	0.24	6,10
8715R	4	14	19/26	0.018	0,46	0.24	6,10
8716R	2	12	19/25	0.018	0,46	0.26	6,60
8717R	3	12	19/25	0.018	0,46	0.27	6,86

Multiconductor, Foil Shielded Riser

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8718R	2	22	7/30	0.018	0,46	0.13	3,30
8719R	3	22	7/30	0.018	0,46	0.14	3,56
8720R	2	20	7/28	0.018	0,46	0.15	3,81
8721R	3	20	7/28	0.018	0,46	0.16	4,06
8722R	2	18	7/26	0.018	0,46	0.16	4,06
8723R	3	18	7/26	0.018	0,46	0.18	4,57
8724R	4	18	7/26	0.018	0,46	0.18	4,57
8725R	2	16	19/29	0.018	0,46	0.19	4,83
8726R	3	16	19/29	0.018	0,46	0.2	5,08
8727R	2	14	19/26	0.018	0,46	0.22	5,59
8728R	3	14	19/26	0.018	0,46	0.25	6,35
8729R	2	12	19/25	0.018	0,46	0.27	6,86

Plenum-Rated PVC


Multiconductor, Unshielded Plenum

Operating Temperature: -20°C to 60°C Voltage Rating: 300 Volt Conductor: Stranded Bare copper Insulation: Color-Coded PVC, Shield: Aluminum/Polyester Foil with a Tinned Copper Drain Wire, Jacket: Plenum Rated PVC UL Types: CMP, MPP, CL2P, FPLP (22 AWG thru 16 AWG) UL Types: CL2P, FPLP (14 AWG and 12 AWG)


Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8701P	2	22	7/30	.014	0,36	0.12	3,05
8702P	3	22	7/30	.014	0,36	0.14	3,56
8703P	4	22	7/30	0.014	0,36	0.14	3,56
8704P	2	20	7/28	0.014	0,36	0.13	3,30
8705P	3	20	7/28	0.014	0,36	0.14	3,56
8706P	4	20	7/28	0.014	0,36	0.15	3,81
8707P	2	18	7/26	0.014	0,36	0.15	3,81
8708P	3	18	7/26	0.014	0,36	0.16	4,06
8709P	4	18	7/26	0.014	0,36	0.17	4,32
8710P	2	16	19/29	0.014	0,36	0.18	4,57
8711P	3	16	19/29	0.014	0,36	0.18	4,57
8712P	4	16	19/29	0.014	0,36	0.2	5,08
8713P	2	14	19/26	0.014	0,36	0.2	5,08
8714P	3	14	19/26	0.014	0,36	0.21	5,33
8715P	4	14	19/26	0.014	0,36	0.24	6,10
8716P	2	12	19/25	0.014	0,36	0.25	6,35
8717P	3	12	19/25	0.014	0,36	0.27	6,86

Multiconductor, Foil Shielded Plenum

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8718P	2	22	7/30	0.014	0,36	0.12	3,05
8719P	3	22	7/30	0.014	0,36	0.13	3,30
8720P	4	22	7/30	0.014	0,36	0.14	3,56
8721P	6	22	7/30	0.014	0,36	0.17	4,32
8722P	8	22	7/30	0.014	0,36	0.18	4,57
8723P	10	22	7/30	0.014	0,36	0.2	5,08
8724P	2	20	7/28	0.014	0,36	0.13	3,30
8725P	3	20	7/28	0.014	0,36	0.14	3,56
8726P	4	20	7/28	0.014	0,36	0.16	4,06
8727P	2	18	7/26	0.014	0,36	0.15	3,81
8728P	3	18	7/26	0.014	0,36	0.17	4,32
8729P	4	18	7/26	0.014	0,36	0.18	4,57
8730P	2	16	19/29	0.014	0,36	0.18	4,57
8731P	3	16	19/29	0.014	0,36	0.19	4,83
8732P	4	16	19/29	0.014	0,36	0.21	5,33
8733P	2	14	19/26	0.014	0,36	0.22	5,59
8734P	3	14	19/26	0.014	0,36	0.23	5,84
8735P	2	12	19/25	0.014	0,36	0.25	6,35



8813-8824



8801-8806



8807-8812

Building Zone, Multipair, Riser-Rated PVC

Multipair, Unshielded Riser

Operating Temperature: -20°C to 60°C • Voltage Rating: 300 Volt Conductor: Stranded Bare Copper, Insulation: Color-Coded PVC, Shield: Overall Foil (Aluminum/Polyester) with a tinned copper drain wire, Individually Shielded: Aluminum/Polyester Foil Each Pair with a Tinned Copper Drain Wire, Jacket: PVC UL Types: CMR, MPR, CL2R, FPLR

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8801R	2	22	7/30	0.018	0,46	0.15	3,81
8802R	3	22	7/30	0.018	0,46	0.20	5,08
8803R	4	22	7/30	0.018	0,46	0.22	5,59
8804R	2	18	7/26	0.018	0,46	0.19	4,83
8805R	3	18	7/26	0.018	0,46	0.26	6,60
8806R	4	18	7/26	0.018	0,46	0.28	7,11

Multipair, Foil Shielded Riser

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8807R	2	22	7/30	0.018	0,46	0.15	3,81
8808R	3	22	7/30	0.018	0,46	0.20	5,08
8809R	4	22	7/30	0.018	0,46	0.22	5,59
8810R	2	18	7/26	0.018	0,46	0.19	4,83
8811R	3	18	7/26	0.018	0,46	0.26	6,60
8812R	4	18	7/26	0.018	0,46	0.28	7,11

Multipair, Individually Foil Shielded Riser

Alpha Part No.	No. of Cond.	Cond. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8813R	2	22	7/30	0.018	0,46	0.21	5,33
8814R	3	22	7/30	0.018	0,46	0.22	5,59
8815R	4	22	7/30	0.018	0,46	0.24	6,10
8816R	6	22	7/30	0.018	0,46	0.28	7,11
8817R	2	20	7/28	0.018	0,46	0.23	5,84
8818R	3	20	7/28	0.018	0,46	0.25	6,35
8819R	4	20	7/28	0.018	0,46	0.27	6,86
8820R	6	20	7/28	0.018	0,46	0.32	8,13
8821R	2	18	7/26	0.018	0,46	0.26	6,60
8822R	3	18	7/26	0.018	0,46	0.28	7,11
8823R	4	18	7/26	0.018	0,46	0.31	7,87
8824R	6	18	7/26	0.018	0,46	0.37	9,40




EDGE



Building Zone Facilities Management Cable



8901-8907



8908-8914

Building Zone, Fire Alarm Cable Riser Rated

Fire Alarm, Unshielded Riser

Operating Temperature: -20°C to 60°C Voltage Rating: 300 Volt
Conductor: Solid bare Copper, Insulation: Color-Coded PVC, Shield:
Aluminum/Polyester Foil with a Tinned Copper Drain Wire, Jacket: PVC
UL Type FPLR , California State Fire Marshall Listed

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8901R	2	18	Solid	0.015	0,38	0.14	3,56
8902R	4	18	Solid	0.015	0,38	0.17	4,32
8903R	2	16	Solid	0.015	0,38	0.19	4,83
8904R	4	16	Solid	0.015	0,38	0.22	5,59
8905R	2	14	Solid	0.018	0,46	0.21	5,33
8906R	4	14	Solid	0.018	0,46	0.25	6,35
8907R	2	12	Solid	0.018	0,46	0.24	6,10

Plenum-Rated

Operating Temperature: -20°C to 60°C Voltage Rating: 300 Volt
Conductor: Stranded Bare Copper, Insulation: Color-Coded PVC,
Shield: Overall Foil (Aluminum/Polyester) with a tinned copper drain
wire, Individually Shielded: Aluminum/Polyester Foil Each Pair with a
Tinned Copper Drain Wire, Jacket: Plenum-Rated PVC UL Types:
CMR, MPR, CL2R, FPLR

Multipair, Unshielded Plenum

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8801P	2	22	7/30	0.014	0,36	0.14	3,56
8802P	3	22	7/30	0.014	0,36	0.19	4,83
8803P	4	22	7/30	0.014	0,36	0.20	5,08
8804P	2	18	7/26	0.014	0,36	0.18	4,57
8805P	3	18	7/26	0.014	0,36	0.25	6,35
8806P	4	18	7/26	0.014	0,36	0.27	6,86

Multipair, Foil Shielded Plenum

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8807P	2	22	7/30	0.014	0,36	0.14	3,56
8808P	3	22	7/30	0.014	0,36	0.19	4,83
8809P	4	22	7/30	0.014	0,36	0.20	5,08
8810P	2	18	7/26	0.014	0,36	0.18	4,57
8811P	3	18	7/26	0.014	0,36	0.25	6,35
8812P	4	18	7/26	0.014	0,36	0.27	6,86

Multipair, Individually Foil Shielded Plenum

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8813P	2	22	7/30	0.014	0,36	0.19	4,83
8814P	3	22	7/30	0.014	0,36	0.20	5,08
8815P	6	22	7/30	0.014	0,36	0.27	6,86
8816P	2	18	7/26	0.014	0,36	0.25	6,35
8817P	3	18	7/26	0.014	0,36	0.27	6,86

Plenum-Rated PVC

Fire Alarm, Unshielded Plenum

Operating Temperature: -20°C to 60°C Voltage Rating: 300 Volt
Conductor: Solid bare Copper, Insulation: Color-Coded PVC, Shield:
Aluminum/Polyester Foil with a Tinned Copper Drain Wire, Jacket:
Plenum-Rated PVC UL Type FPLR

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8901P	2	18	Solid	0.014	0,36	0.14	3,56
8902P	4	18	Solid	0.014	0,36	0.16	4,06
8903P	2	16	Solid	0.014	0,36	0.16	4,06
8904P	4	16	Solid	0.014	0,36	0.19	4,83
8905P	2	14	Solid	0.014	0,36	0.19	4,83
8906P	4	14	Solid	0.014	0,36	0.22	5,59
8907P	2	12	Solid	0.014	0,36	0.22	5,59

Fire Alarm, Foil Shielded Riser

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8908R	2	18	Solid	0.02	0,51	0.17	4,32
8909R	3	18	Solid	0.02	0,51	0.19	4,83
8910R	4	18	Solid	0.02	0,51	0.20	5,08
8911R	2	16	Solid	0.02	0,51	0.19	4,83
8912R	4	16	Solid	0.02	0,51	0.22	5,59
8913R	2	14	Solid	0.02	0,51	0.23	5,84
8914R	4	14	Solid	0.02	0,51	0.27	6,86

Fire Alarm, Foil Shielded Plenum

Alpha Part No.	No. of Cond.	Cond. AWG. Size	Stranding	Jacket Thickness		Diameter	
				Inches	mm	Inches	mm
8908P	2	18	Solid	0.14	0,36	0.14	3,56
8909P	3	18	Solid	0.14	0,36	0.15	3,81
8910P	4	18	Solid	0.14	0,36	0.16	4,06
8911P	2	16	Solid	0.14	0,36	0.16	4,06
8912P	4	16	Solid	0.14	0,36	0.19	4,83
8913P	2	14	Solid	0.14	0,36	0.19	4,83
8914P	4	14	Solid	0.14	0,36	0.22	5,59

