



**New Item**

81-011-1

### ANALOG MULTIMETER

- \*Audible continuity checker
- \*db output
- \*hFE test
- \*Mirror scale
- \*c/w Test leads & battery

D.C. Volts: .1, .5, 10, 50, 250, 1KV (3% 20KΩ/V)  
 A.C. Volts: 10, 50, 250, 1KV (4% 9KΩ/V)  
 D.C. Current: 50μA, 2.5mA, 25mA, 250mA (3%)  
 Resistance: x1, x10, x100, x1K, x10K  
 Size: 150 x 100 x 36mm (280g)



**New Item**

81-022-1

### DIGITAL MULTIMETER

- \*3 1/2 Digits
- \*Audible continuity test
- \*Transistor test
- \*Diode test
- \*c/w Test leads & battery

D.C. Volts: 200mV, 2, 20, 200, 600V (.5%)  
 A.C. Volts: 200mV, 2, 20, 200, 700V (.8%)  
 D.C. Current: 20μA, 200μA, 2mA, 20mA, 200mA, 2A, 10A (.8%)  
 A.C. Current: 20μA, 200μA, 2mA, 20mA, 200mA, 2A, 10A (1%)  
 Resistance: 200, 2K, 20K, 200K, 2MΩ (.5%)  
 Size: 88 x 172 x 36mm



**New Item**

81-020-1

### POCKET DIGITAL MULTIMETER

- \*3 1/2 Digits
- \*Diode test
- \*Transistor test
- \*Protective holster
- \*c/w Test leads & battery

D.C. Volts: 200mV, 2, 20, 200, 600V (.5%)  
 A.C. Volts: 200, 600V (1.2%)  
 D.C. Current: 200μA, 2mA, 20mA, 200mA, 10A (1%)  
 Resistance: 200, 2K, 20K, 200K, 2MΩ (.8%)  
 Size: 70 x 126 x 24mm



**New Item**

81-023-1

### DIGITAL MULTIMETER

- \*3 1/2 Digits
- \*Flip-up Display
- \*Audible continuity test
- \*Capacitance
- \*Transistor test
- \*Diode test
- \*Protective Holster
- \*c/w Test leads & battery

D.C. Volts: 200mV, 2, 20, 200, 1000V (.5%)  
 A.C. Volts: 200mV, 2, 20, 200, 700V (.8%)  
 D.C. Current: 2mA, 20mA, 200mA, 2A, 20A (.8%)  
 A.C. Current: 20mA, 200mA, 2A, 20A (1%)  
 Resistance: 200, 2K, 20K, 200K, 2M, 20M, 200MΩ (.8%)  
 Capacitance: 2n, 20n, 200n, 2μA, 20μF (4%)  
 Size: 91 x 192 x 42mm



**New Item**

81-021-1

### POCKET DIGITAL MULTIMETER

- \*3 1/2 Digits
- \*Diode test
- \*Continuity test
- \*Battery
- \* Test leads wrap around meter

D.C. Volts: 2, 20, 200, 500V (.5%)  
 A.C. Volts: 2, 20, 200, 500V (1.2%)  
 D.C. Current: 200mA (1.5%)  
 Resistance: 2K, 20K, 200K, 2MΩ (1%)  
 Size: 70 x 120 x 18mm



**New Item**

81-024-1

### DIGITAL MULTIMETER

- \*3 3/4 Digits
- \*Data Hold
- \*Bar Graph
- \*Audible continuity test
- \*Frequency
- \*Capacitance
- \*Transistor test
- \*Diode test
- \*Protective Holster
- \*c/w Test leads & battery

D.C. Volts: 326mV, 3.26, 32.6, 326, 1000V (.5%)  
 A.C. Volts: 3.26, 32.6, 326, 750V (.8%)  
 D.C. Current: 326μA, 3.26mA, 32.6mA, 326mA, 10A (1.2%)  
 A.C. Current: 326μA, 3.26mA, 32.6mA, 326mA, 10A (1.5%)  
 Resistance: 326, 3.26K, 32.6K, 326K, 3.26M, 32.6M (.8%)  
 Capacitance: 326nF - 32.6μF (4%)  
 Frequency: 32.6K - 150KHz  
 Size: 91 x 189 x 31mm

## LIMITED THREE YEAR WARRANTY

All Mode meters are warranted to be free of defects in materials & workmanship for a period of three years from date of purchase. We will replace or repair any meter determined by Mode to be defective under these conditions. Warranty is void if we determine the meter has been abused or operated in a careless manner. Batteries and test leads not included. Dated proof of purchase required.



**New  
Item**

**81-025-1**

**DIGITAL  
MULTIMETER**

- \*3 1/2 Digits
- \*Data Hold
- \*Audible continuity test
- \*Frequency
- \*Capacitance
- \*Transistor test
- \*Diode test
- \*c/w Test leads & battery

D.C. Volts: 200mV, 2, 20, 200, 1000V (.8%)  
 A.C. Volts: 200mV, 2, 20, 200, 750V (1.2%)  
 D.C. Current: 200µA, 2mA, 20mA, 200mA, 10A (1%)  
 A.C. Current: 200µA, 2mA, 20mA, 200mA, 10A (1%)  
 Resistance: 200, 2K, 20K, 200K, 2M, 20MΩ (1.5%)  
 Capacitance: 2n, 20n, 200n, 2µA, 20µF (3%)  
 Frequency: 2K, 20K, 200K, 2M, 20MHz (.5%)  
 Size: 74 x 153 x 45mm



**New  
Item**

**81-040-1**

**DIGITAL  
THERMOMETER**

- \*3 1/2 Digits
- \*-50 to 750 Degrees C
- \*.75% Accuracy
- \*K' Thermocouple
- \*c/w Battery

Size: 24 x 72 x 108mm



**New  
Item**

**81-050-1**

**DIGITAL CLAMP-ON  
METER**

- \*3 1/2 Digits
- \*Audible continuity test
- \*Soft carrying case
- \*c/w Test leads & battery

D.C. Volts: 2, 20, 200, 1000V (.5%)  
 A.C. Volts: 200, 600V (1%)  
 A.C. Current: 20, 600, 1000A (2%)  
 Resistance: 200, 2K, 20K, 200K, 2M (1%)  
 Size: 70 x 230 x 37mm



**New  
Item**

**81-026-1**

**DIGITAL  
MULTIMETER**

- \*3 1/2 Digits
- \*Data Hold
- \*Audible continuity test
- \*Frequency
- \*Capacitance
- \*Temperature
- \*Transistor test
- \*Diode test
- \*c/w Test leads & battery

D.C. Volts: 200mV, 2, 20, 200, 1000V (.8%)  
 A.C. Volts: 200mV, 2, 20, 200, 750V (1.2%)  
 D.C. Current: 200µA, 2mA, 20mA, 200mA, 10A (1%)  
 A.C. Current: 200µA, 2mA, 20mA, 200mA, 10A (1.5%)  
 Resistance: 200, 2K, 20K, 200K, 2M, 20MΩ (1%)  
 Capacitance: 2n, 20n, 200n, 2µA, 20µF (3%)  
 Frequency: 2K, 20K, 200K, 2M, 20MHz (.5%)  
 Temperature: 300 C / 572 F (requires thermocouple)  
 Size: 74 x 153 x 45mm



**New  
Item**

**81-051-1**

**DIGITAL PLUG-IN  
CLAMP-ON HEAD**

This clamp-on plugs into any digital multimeter with a 3.2 VAC range. It will measure AC current from 3A to 300A. Comes c/w protective carrying case.

Size: 80 x 156 x 35mm



**New  
Item**

**81-031-1**

**DIGITAL  
CAPACITANCE**

- \*3 1/2 Digits
- \*.5% Accuracy
- \*Protective Holster
- \*c/w Clip leads & battery

Capacitance: 200p, 2n, 20n, 200n, 2µA, 20µF, 2000µF (3%)  
 Size: 91 x 189 x 31mm



**New  
Item**

**81-060-1**

**DIGITAL  
LIGHT METER**

- \*3 1/2 Digits
- \*Lux or Foot Candles

Lux Range: 0.1 - 50,000 Lux  
 Fc Range: .01 - 5,000 Fc

**LIMITED THREE YEAR WARRANTY**

All Mode meters are warranted to be free of defects in materials & workmanship for a period of three years from date of purchase. We will replace or repair any meter determined by Mode to be defective under these conditions. Warranty is void if we determine the meter has been abused or operated in a careless manner. Batteries and test leads not included. Dated proof of purchase required.